

BREEZE TOUCH MONITOR



Highlights

- Serial and USB Touch Interface
- External Power Supply, Hidden in Base
- Excellent Cable Management
- Elo Resistive Touch
- Internal Speakers
- Available in 15" or 17"

Options

- Integrated MSR
- Integrated Digital Persona UareU
- Rear Customer Display

Designed to Provide Enhanced Computing Performance and Versatility

The Breeze Touch Monitor comes in Serial and USB Touch interface. It has an external power supply which is hidden in base. It provides an excellent solution for cable management.



LCD Panel

- LCD Size - 15" or 17"
- Brightness - 250nits
- Maximum Resolution - 15": 1024 x 768,
17": 1280 x 1024
- Touch Screen Type - Elo Resistive
- Tilt Angle - 0° - 70°

Peripheral Options

- MSR - 3 tracks (PS/2 or USB interface)
- Biometric Reader - Integrated Digital Persona
- Customer Display - 2 x 20 VFD (COM)
- Biometric - Integrated Digital Persona
- Speakers - 2 x 2 Watt internal speakers

Power Adapter

- Power Supply - 36W(12V/3A Max)

External I/O

- VGA - 1
- Serial Ports - 2 (1xDB9 RS-232, 1 xRJ45 out for VFD)
- USB - 1 x USB out, 1 USB in (B type)
- OSD Button - 2
- PS/2 - 1

Environment

- EMC & Safety - FCC/CE Class A, LVD
- Operating Temperature - 41°F - 113°F
- Storage Temperature - -4°F - 140°F
- Operating Humidity - 5% - 95% non condensing
- Storage Humidity - 5% - 95% non condensing
- Dimensions - LCD 0 - 14.7 x 10 x 14.5 in
- with base 16.85 x 13.45 x 9.9 in
- Weight - 15Lbs
- Mounting - 100 x 100 VESA mount

