

TP 3000 Thermal Printer



Compact Thermal Printer

The TP3000 Thermal Receipt Printer was designed for rugged POS applications. It boasts Jam Free Autocutter technology. This TP3000 now incorporates dual interface IO cards as well!

Options Include...

Features

- Direct Thermal
- Drop in Paper Loading
- High Speed Printing (200mm/s)
- Bar Code Printing
- Epson Compatible

Dual Interface Options

- Serial / USB
- Ethernet / USB
- Parallel / USB



TP 3000



TP3000 Specifications

Print Method		Direct thermal
Print Speed		200mm/sec
Print Buffer		4K (can be increased to 12K on special order)
Dot Density		180DPI x 180DPI
Dot Pitch		0.141mm x 0.141mm
Effective Printing Width		72mm, 512 Dots/line
Printing Direction		Unidirectional with friction feed
Character per Line		Font A (12x24) 42 columns / Font B (9x17) 58 columns
Paper	Type	Thermal Paper
	Width	50mm ~ 82.5mm (2in ~ 3.5in)
	Thickness	0.06 ~ 0.09mm
	Roll Diameter	Max 80mm (3.5in)
Reliability	Tph Life	160Km
	Mcbf	60,000,000 lines
Character Set	Alphanumeric Character	95
	Extended Graphic	128x18 page
	International Character	14
Barcode		EAN-8, EAN-13, CODE39, ITF, UPC-A, CODEBAR, CODE 93, CODE 128, PDF417(20)
Emulation		ESC/POS COMMAND COMPAT- IBLE
Drawer Port		1 Port
Interface Options		Serial / USB, Parallel / USB, Ethernet / USB
Power	Type	Extrenal SMPS
	AC	100-240V 50/60Hz
	DC	24V / 2.5A
Dimension	W x D x H	6.3 x 8.5 x 6.25 in
Weight	Includes Auto Cutter	3.75lbs

